

84375

S/106/60/000/006/008/013

A169/A026

X

The Long-Distance Tropospheric Propagation of Ultrashort Waves

the earth's surface, is of great practical importance, since it permits a determination of the mean signal levels of routes, whose terminal points are located in different geographic districts, by the value of ϵ_0 without that special measurements have to be made. The value of ϵ_0 can be easily determined from meteorological data. In some experiments, however, a correlation between the mean signal level and ϵ_0 was not found. Consequently, problems in predicting the mean signal levels in different geographic districts on the basis of meteorological data necessitate further research. Up to now, the effect of meteorological conditions on the signal level in long-distance tropospheric propagation of ultrashort waves has not yet been sufficiently studied. In the majority of cases, the passage of a front causes a decrease in the signal level, which can be explained by a greater perturbation of the troposphere. In some cases, however, the signal level increases during the passage of a front, caused by a reflection of waves at the border between cold and warm air layers. There are 13 figures and 3 references: 2 English and 1 Soviet.

SUBMITTED: March 3, 1960

Card 4/4

Kalinin, A.I.
9,9000

82180
S/106/60/000/07/04/005

AUTHOR: Kalinin, A.I.

TITLE: The Long-Distance Tropospheric Propagation of Ultrashort Waves
(A Theoretical Discussion of Experimental Results)

PERIODICAL: Elektrosvyaz', 1960, No. 7, pp. 38 - 46

TEXT: The author presents a theoretical discussion of experimental data on the long-distance tropospheric propagation of ultrashort waves which he described in a previous paper (Elektrosvyaz', 1960, No. 6). The long-distance propagation of ultrashort waves is caused by nonuniformities of the troposphere, re-radiating the electromagnetic energy, a part of which will arrive in the area of reception. These nonuniformities are caused by the complicated structure of the troposphere, resulting from fluctuations of temperature, humidity and air pressure, as well as from the turbulent motion of the air and air layer formation. The turbulent motion of the air is caused by irregular heating and unevenness of the earth's surface. The theory of turbulency was developed by the Soviet scientists A.N. Kolmogorov and A.M. Obukhov. The layer formation in the troposphere is caused by gravitational forces and by the different density of the air at different altitudes. These layer formations are more stable and have

Card 1/3

X

82180

S/106/60/000/07/04/005

The Long-Distance Tropospheric Propagation of Ultrashort Waves (A Theoretical Discussion of Experimental Results)

larger horizontal dimensions than the turbulent air masses. The dielectric constant of the air fluctuates within certain ranges and at irregular intervals, depending upon the structure of the troposphere and the state of the air. The irregular decrease of the dielectric constant with increasing altitude was established by measurements with aircraft refractometers. The layer formation limits the turbulent motion of the tropospheric air, but in turn, the air turbulence causes a perturbation of the air layer formation. Presently, numerous papers are available, in which attempts were made to give a theoretical explanation of experimental data on tropospheric long-distance propagation of ultrashort waves. These theories can be divided into a coherent and into an incoherent class. A detailed discussion of these theories is not given. The experimental results obtained on the tropospheric long-distance propagation of ultrashort waves are discussed from the viewpoints of the aforementioned classes of theories, especially: 1) the dependence of the mean signal level on the distance and the antenna height; 2) the correction between the mean signal level and the value of the dielectric constant of the air on the ground and with a vertical gradient, including seasonal changes of the signal level; 3) the dependence of the signal level on the wavelength; 4) the effect of the type of

Card 2/3

X

82180

S/106/60/000/07/04/005

The Long-Distance Tropospheric Propagation of Ultrashort Waves (A Theoretical Discussion of Experimental Results)

radio wave polarization; 5) the widening of the directivity pattern of antennas⁷⁵³ and the phenomena of antenna gain loss. The available experimental results on the long-distance propagation of ultrashort waves and the operation of the first radio relay lines based on this phenomenon lead to the conclusion that such communication lines can be established on a larger scale. However, a sufficiently complete theory, quantitatively describing all regularities established by experimental investigations, has not yet been found. So far, not even an agreement of opinions has been obtained on the mechanism of such a long-distance propagation. There are 8 diagrams.

SUBMITTED: April 2, 1960

X

Card 3/3

S/108/60/015/06/01/006
B007/B014

AUTHOR: Kalinin, A. I., Member of the Society (*NuRIE*)

TITLE: Statistical Distribution of the Fading Depth at the
Intervals of Radio Relay Lines

PERIODICAL: Radiotekhnika, 1960, Vol. 15, No. 6, pp. 3-9

TEXT: In a preceding paper (Ref. 1) the author gave a graphic-analytical method for the drawing of integral curves of the fading-depth distribution and an analytical formula for the stability curves corresponding to operations within the limits of the first interference leaf. In the article under review, the author derives a general formula for the integral curves of the fading-depth distribution and the limiting formulas for these curves. As in Ref. 1, it is assumed that the fading is caused by interference of the direct wave and by the wave reflected from the earth's surface. The non-linear dependence of the dielectric constant ϵ of the air upon the height and the non-homogeneity of ϵ in the horizontal direction are taken into account by introducing the effective vertical

B

Card 1/3

Statistical Distribution of the Fading Depth S/108/60/015/06/01/006
at the Intervals of Radio Relay Lines B007/B014

gradient of ϵ of the air which was obtained from radiotechnical measurements (Ref. 2). In Ref. 3 the author showed that the field-attenuation factor of a free space V is expressed by two parameters, $p(g)$ and μ . These parameters are determined from formulas (1) - (2) and/or (5). At $p(g) < 1$, formula (8) holds for the relation between V and $p(g)$, whereas formula (9) holds for $p(g) > 1$. Next, formula (23) is derived for the period $T(V)$ within which the attenuation factor is smaller than V . The total time $T(V)$ is composed of $T_o(V)$ and $T_n(V)$. The former is the time in which the attenuation factor is smaller than V because the point of reception is in the zone $p(g) < 1$. $T_n(V)$ is the time in which the attenuation factor is smaller than V because the point of reception is near the interference minima ($p(g) > 1$). Formula (26) is derived for $T_n(V)$; the value of $T_n(V)$ determined from this formula is substituted into formula (23), and formula (30) is obtained. When m is great (number of the interference maximum), $T_o(V)$ in formula (30) is negligible, and one obtains formula (32). Assuming that $|\phi_n| = 1$, one obtains formula (33):

$T(V) = f(A, m)V$. $|\phi_n|$ is the modulus of the reflection coefficient for

Card 2/3

Statistical Distribution of the Fading Depth S/108/60/015/06/01/006
at the Intervals of Radio Relay Lines B007/B014

the n-th minimum. $|\Phi|$ is the modulus of the coefficient of reflection from the earth's surface. The limits of the series $f(A, m)$ are then determined. Fig. 2 gives a diagram for the determination of the function $f(A, m)$. Stability curves for lines of 40, 60, and 80 km and waves of 8 and 16 cm are shown in Figs. 3-6. These curves were drawn on the assumption that the earth is a perfect sphere. It is shown that with sufficiently long lines and small wavelengths the actual stability curves will be found between the two curves described by formulas (40) and (41). There are 6 figures and 5 Soviet references.

SUBMITTED: May 25, 1959

Card 3/3

22257

S/109/61/006/0001/004/027
D201/D303

6,4200

AUTHOR: Kalinin, A.I.

TITLE: Influence of earth in the long-distance tropospheric propagation of ultrashort waves

PERIODICAL: Radiotekhnika i elektronika, v. 6, no. 5, 1961,
723 - 727

TEXT: In his previous work (Ref. 1: Kogerentnaya Teoriya dal'nego troposfernogo rasprostraneniya ul'trakorotkikh voln, Elektrosvyaz' 1959, 6, 41) the author showed that the experimentally determined mechanism of the tropospheric propagation of ultrashort waves may be explained by the waves being reflected from the upper half space according to an exponential dependence of the specific inductive capacitance of air ϵ on the height h above the earth's surface. In the present article the author solves the problem of determining the mean value of the field intensity in tropospheric propagation of USW, based on the hypothesis of a coherent reflection from the

X

Card 1/5

22257

S/109/61/006/005/004/027
D201/D303

Influence of earth in ...

stratified inhomogeneities of the troposphere, on the exponential dependence of specific inductive capacitance of the air on the height and taking into account the diffraction around the earth's surface. The problem is solved by assuming the vertical antenna to be at the surface of an ideally conducting earth. The solution is further based on results given by V.A. Fok (Ref. 4: Difraktsiya radiovoln vokrug zemnoy poverkhnosti (Diffraction of Radio Waves around the Earth's Surface) Izd. AN SSSR, 1946) who for a vertical radiator placed at the surface of an ideally conducting earth and for $y \gg 1$ (y - height h in dimensionless units) obtained the following expression for the attenuation function

$$U(y) = \sqrt[4]{\frac{x^3}{4y}} \exp\left(i \frac{2}{3} y^{\frac{3}{2}}\right) V_1(z), \quad (6)$$

where, x - distance in dimensionless units: $x = \frac{R}{R_0}$, R_0 - the 'standard' distance

Card 2/5


S/109/61/006/005/004/027
D201/D303

Influence of earth in ...

$$R_0 = \sqrt{\frac{a_e}{\pi}} \quad (8)$$

$$z = \frac{\pi}{2} - \sqrt{y} \quad (9)$$

(where λ is the wavelength and a_e - the equivalent radius of the earth) and $V_1(z)$ - the attenuation function of a plane wave, the graphs of which are given in Fig. 2a, b,



Card 3/5

S/109/61/006/005/004/027

D201/D303

Influence of earth in...

as taken from the work by P.A. Azrilyant, and M.G. Belkina (Ref. 5: Chislennye rezul'taty teorii diffraktsii radiovoln vokrug zemnoy poverkhnosti (Numerical Results of the Theory of Diffraction of Radiowaves around the Earth's Surface) Izd. Sovetskoye Radio, 1957). Taking again the results obtained by V.A. Fok (Ref. 4: Op.cit.) for large values of z , $V_1(z)$ becomes eventually after several mathematical transformations and in good approximation

$$|V| = 2.24 \frac{1}{2\pi} \frac{\Delta g}{R^2} \exp\left(\frac{Rg}{8\pi\Delta e_0}\right). \quad (27)$$

where g is the value of the gradient of the inductive capacitance of air near the earth's surface. The value of the modulus of the attenuation factor in Eq. (27) differs from the corresponding value of $|V|$ in the previous work by the author only by a constant factor 2.24. If for the given case the transition region between the two semi-spaces be ideally short, the above factor should have been 4. It follows that the spread in the transition region produces a

Card 4/5

9,9300 (1344)

24460

S/109/61/006/006/001/016
D204/D303

AUTHORS: Armand, N.A., Vvedenskiy, B.A., Kalinin, A.I.,
Kolosov, M.A., Sokolov, A.V., Shabel'nikov, A.V.,
and Shirey, R.A.

TITLE: A survey of work on the tropospheric propagation of
ultrashort radiowaves

PERIODICAL: Radiotekhnika i elektronika, v. 6, no. 6, 1961,
867 - 885

TEXT: The large body of experimental work done in this field has
been aided by the perfecting of apparatus and auxiliary instru-
ments and given impetus by the need for more knowledge to assist
the development of telephony, television and radio communications.
The authors examine the following: 1) Relations between field
strength and distance; 2) Signal level and frequency: the theore-
tical picture is confused, state the authors, but most experimen-
tal work suggests that P_r/P_o (P_r - received power, P_o - value in

Card 1/8

24460

A survey of work on the ...

S/109/61/006/006/001/016
D204/D303

free space) declines as the frequency rises. No uniform value of $P_r(\lambda)$ has been found as yet, probably because of the changeability of the tropospheric structure and meteorological conditions; 3) Signal and time: Signal fading may be rapid or slow. Most information concerns 300 - 500 km traces. Slow fading is caused by the appearance or disappearance of inversion layers, large irregularities and changes in the value of $d\varepsilon/dh$. Usually the signal strength is greater in the evening and at night, clearer in summer than in winter and at shorter (100-150 km) rather than longer (400 - 500 km) distances. The amplitude is related to frequency; also, as it combines with slow fading, the average amount of fading increases reaching, according to some sources, a maximum at 100-130 km. Others maintain that it declines with increase in distance to an equal summer and winter value of 3 - 10 db at 900 km; 4) Loss of antennae amplification: The phenomenon occurs beyond the horizon and means that for an antenna with an amplification coefficient G, exceeding 35-40 db, amplification is less than in free space. To account for this there are two hypotheses: (1) Spreading of radio-

Card 2/8

24460

A survey of work on the ...

S/109/61/006/006/001/016
D204/D303

waves in a statistically non-homogeneous medium leads to distortion of the wave front in the plane of the receiving antenna and thus the energy absorbed is less than in the absence of amplitude and phase fluctuation, (2) elementary waves with various random angles of approach may reach the receiving antenna. These hypotheses have been investigated but comparison of results is hampered by differences in experimental conditions. For a 300 km trace the amplification loss increases with increase in the average amplification of receiving and transmitting antennae and with an increase of D to 300 - 500 km and $f = 2290$ megacycles. At greater distances the loss falls; 5) Signal distortion: Work in this field either treats the troposphere as an ideal quadruple network or aims to determine the amplitude correlation of the signal components on different frequencies in the transmitted spectrum. If with antennae with low directivity the amplitude of delayed waves is diminished by diffraction weakening of the earth's surface and the "directivity" of the troposphere, then at antennae with narrow patterns the amplitude of these waves decreases because of the di-

+
+

Card 3/8

24460

A survey of work on the ...

S/109/61/006/006/001/016
D204/D303

+
+

rectivity of the antenna. The maximum transmitted frequency band depends on the width of the directivity pattern of the antenna. The random nature of the tropospheric radiation means that signal distortion has a random pattern as experiments in the USSR have confirmed. Two separated antennae in space diminish distortion and guarantee a large carrying capacity of tropospheric radio links;
6) Radio-meteorological research: Refractometric measurements have dealt with the structure of the troposphere and, in particular, the value of $\varepsilon(h)$, $(\Delta \varepsilon)^2$ and the area of turbulence

$$1 \sqrt{(\Delta \varepsilon)^2}$$

usually varies within the range 0.3 - 3N units and irregular layers are usually 1 - 300 m thick. "Jump" intensity in these regions is usually 2 - 50 or 60 N units, large especially in the "invisible clouds". It was stated that at a height $h = 3000$ m and more $(\Delta \varepsilon)^2/1$ is too small to explain distant fields and its alteration with height does not give the necessary value of $P_r(D)$. The authors

Card 4/8

A survey of work on the ...

24460
S/109/61/006/006/001/016
D204/D303

then deal with incoherent scatter and globular irregularities: In the last few years much attention has been devoted to the conception of incoherent scatter. Two chief theories have been established; One which gives for the frequency subordinate of P_r/P_o , a coefficient of $\lambda^{7/3}$, and the theory of "disturbance of the gradient", which gives λ . The second approaches more closely to the experimental facts, and is generally preferred. Maxwell's equations for statistically non-homogeneous layers above a spherical earth have not yet been resolved and a solution must combine the theory of diffraction spread with pereoptical theory. All theories, in essence, approach those of a "radar form type"

$$\frac{P_r}{P_o} = QD^2 \int_v \frac{\sigma(\theta)}{R_1^2 R_2^2} dV, \quad (1)$$

where Q is a constant factor; $\sigma(\theta)$ - "scatter area" - a junction for the influence of fluctuation ϵ and its relation to λ and the

Card 5/8

A survey of work on the ...

24160
S/109/61/006/006/001/016
D204/D303

gradient $d\varepsilon/dh$; with this formula theory discrepancy concerns basically the value of σ . σ , moreover, can be expressed simply as

$$\sigma(\theta) = \frac{b}{\sin^{\frac{m}{2}}(\frac{\theta}{2})},$$

where θ - radiation angle, equal to the angular distance between transmitter and receiver; b - expression giving ratios of 1, $d\varepsilon/dh$ and others to $(\Delta\varepsilon)^2$. For whole even numbers $m > 2$ this accords well with a general formula and is integrated with formula 2 to give

$$\frac{P_r}{P_0} = Q b A_m D^{-m+3}, \quad (2)$$

where A_m depends on m . If $b \approx h^{-n}$, then $D^{-m+3-2n}$ replaces D^{-m+3} ; m can be substituted by nearest even whole number, in cases of close approximation. Current theories give results approximate to

Card 6/8

21160
S/109/61/006/006/001/016
D204/D503

A survey of work on the ...

was obtained, where Φ is a complicated function, analogous to the high factors of classical diffraction theory, containing frequency responses and 'jump' ratios $[\frac{d\phi}{dh}]_0$; a = another function of type $A - B \ln \lambda$ related to parameters, whose size A and B does not depend on λ . Though not strictly accurately descriptive of the fluctuation character of the field the equation gives the necessary experimental ratio $P_r(D)$. There are 9 figures and 119 references: 24 Soviet-bloc and 97 non-Soviet-bloc. The four most recent references to the English-language publications read as follows: Radio transmission by ionospheric and tropospheric scatter, Proc. I.R.E., 1960, 48, 1, 30; E.D. Denman, Proc. I.R.E., 1960, 48, 1, 112; I.H. Vogelman, I.L. Ryerson, M.H. Bickelhaupt, Proc. I.R.E., 1959, 47, 5, 688; L.A. Ames, E.T. Martin, E.J. Rogers, Proc. I.R.E., 1959, 47, 5, 769.

SUBMITTED: July 27, 1960

Card 8/8

ACCESSION NR: AP4042500

S/0106/64/000/007/0001/0012

AUTHOR: Kalinin, A. I.; Troitskiy, V. N.; Shur, A. A.

TITLE: Statistical characteristic of a signal during long-range propagation of ultrashort waves

SOURCE: Elektrosvyaz', no. 7, 1964, 1-12

TOPIC TAGS: tropospheric wave attenuation, slow signal fading, signal statistical characteristic, wide band transmission, spacial correlation radius, frequency correlation radius, fading statistical distribution

ABSTRACT: The results are presented of an investigation of long-range tropospheric propagation. Measurements were made at 30-40-cm wavelengths along routes 159, 303, 448, 630, and 730 km in length and at 8-9-cm wavelengths along routes 85, 205, and 303 km in length. Receiver-transmitter equipment and antennas used made it possible to measure the attenuation factor $V = -118$ db for the 30-40-cm wavelength along the 730 km route and $V = -106$ db for the 8 to 9-cm wavelength along the 303 km route. The error of measuring signal-level values did not exceed ± 1.5 db. According to the experiments, 1/2.

Care

ARMAND, N.A.; VVEDENSKIY, B.A.; GUSYATINSKIY, I.A.; IGOSHEV, I.P.;
KAZAKOV, L.Ya.; KALININ, A.I.; KOLOSOV, M.A.; LEVSHIN, I.P.;
LOMAKIN, A.N.; NAZAROVA, L.G.; NEMIROVSKIY, A.S.; PROSIN,
A.V.; RYSKIN, E.Ya.; SOKOLOV, A.V.; TARASOV, V.A.; TRASHKOV,
P.S.; TIKHOMIROV, Yu.A.; TROITSKIY, V.N.; FEDOROVA, L.V.;
CHERNYY, F.B.; SHABEL'NIKOV, A.V.; SHIREY, R.A.; SHIFRIN, Ya.S.;
SHUR, A.A.; YAKOVLEV, O.I.; ARENBERG, N.Ya., red.

[Long-distance tropospheric propagation of ultrashort radio
waves] Dal'nee troposfernoe rasprostranenie ul'trakorotkikh
radiovoln. Moskva, Sovetskoe radio, 1965. 414 p.
(MIRA 18:9)

I. 4706-65 EWT(1)/EWA(h) PI-4/Feb

UR/0108/65/020/004/0045/0049

20

ACCESSION NR: AP5010381

B

AUTHOR: Malinin, A. I. (Active member); Matyushin, A. T. (Active member)

TITLE: Some possibilities of compound correction of the amplitude-frequency characteristic of an amplifier

SOURCE: Radiotekhnika, v. 20, no. 4, 1965, 45-49

TOPIC TAGS: amplifier, electron tube amplifier, rf amplifier, ⁴⁵ amplitude frequency characteristic, amplitude correction

ABSTRACT: As an autotransformer-type 4th and 5th order correction circuit based on the "smooth approximation" method suggested by R. A. Müller (FILE, v. 42, no. 3, 1954) is difficult to materialize (because of the high coupling coefficient required), this article proposes the "Chebyshev approximation" which ensures a maximum frequency band. The general solution of the Chebyshev equation being too difficult to achieve, a particular problem is solved by

Card 1/2

L 47069-65
ACCESSION NR: AP5010381

determining the coefficients in the equation for the frequency-distortion modulus by a trial-and-error method. In preliminary experiments, with a 4th order correction, a frequency band of 100 Mc was obtained (gain, 40 db; irregularity, ± 1 db) which amounted to about 90% of the theoretical limit. It is believed that, with a permissible irregularity of 1.5 db, the full theoretically possible frequency band can be materialized; with an irregularity of 1 db, the band is narrower but is still 30--40% wider than that obtainable from the "smooth approximation" method. Orig. art. has: 6 figures and 11 formulas.

ASSOCIATION: Nauchno-tehnicheskoye obshchestvo radiotekhniki i elektrosvyazi
(Scientific and Technical Society of Radio Engineering and Electromunication)

SUBMITTED: 21Mar63

ENCL: 00

SUB CODE: EG

NO REF SCV: 002

OTHER: 005

MCC
Card 212

L 19371-66 EWT(m) DIAAP GS/RM

ACCESSION NR: AT5013654

UR/0000/65/000/000/0176/0179

543.53 + 68.074, 7:546.284

AUTHOR: Kalinin, A. I.; Kuznetsov, R. A.; Moiseyev, V. V.

10 BH

TITLE: Radioactivation analysis of silicon dioxide by means of ion exchange chromatography. Part 4. Separation of elements on an anion exchanger from solution of hydrofluoric acid and a mixture of hydrofluoric and hydrochloric acid

SOURCE: AN SSSR. Otdeleniye obshchey i tekhnicheskoy khimii. Radiokhimicheskiye metody opredeleniya mikroelementov (Radiochemical methods for determining trace elements); sbornik statey. Moscow, Izd-vo Nauka, 1965, 176-179

TOPIC TAGS: column chromatography, anion exchange resin, radioactivation analysis, silica analysis, halide separation

ABSTRACT: The salts of arsenic, phosphorus, tungsten, antimony, molybdenum, tin, and tantalum are characterized by a complex chromatographic behavior due to their tendency to hydrolyze and to the existence of these ions in several stable oxidation states. In order to minimize the hydrolysis, solutions of HF and HF-HCl mixtures were used for the ion-exchange separation on the AV-17 resin (see Figs. 1 and 2 of the Enclosure). The procedure employed is described. To determine the extent of separation of the elements, radioactive

Card 1/4

L 19371-66

ACCESSION NR: AT5013654

tracers in artificial mixtures were employed. A complete separation was achieved if the activity of the separated fractions did not exceed 10^5 counts per min. The time required for the separation of P, As, W, Sb, Sn, Mo, and Ta was 1.5 to 2 hours. Orig. art. has: 2 figures and 1 table.

ASSOCIATION: None

SUBMITTED: 07Apr64

ENCL: 02

SUB CODE: IC, GC

NO REF SOV: 002

OTHER: 003

2/4

Card

L-19371-66

ACCESSION NR: AT5013654

ENCL: 01




Fig. 1. - Separation of antimony, molybdenum, tin, and tantalum on an anion exchanger in Cl^- form (AV-17 resin, column diameter 2 mm, height of resin layer, 60 mm).

Card 3/4

L 19371-66

ACCESSION NR: AT5013654

ENCL: 02




Fig. 2. - Separation of phosphorus, arsenic, and tungsten on an anion exchanger in F⁻ form (resin AV-17, column diameter 2mm, height of resin layer 60 mm).

Card

4/4 BG

L 19352-66

EWT(M)/ETC(f)/EWG(m)/EWP(t) IJP(c) DS/JD/JG/GS/RM

ACCESSION NR: AT5013655

UR/0000/65/000/000/0180/0181

543.53 + 66.074.7:546.284

AUTHOR: Kalinin, A. I.; Kuznetsov, R. A.; Moiseyev, V. V.; Sokolova, M. N.

TITLE: Radioactivation analysis of silicon dioxide by means of ion-exchange chromatography. Part 5. Separation and determination of alkaline earth metals

SOURCE: AN SSSR. Otdeleniye obshchey i tekhnicheskoy khimii. Radiokhimicheskiye metody opredeleniya mikroelementov (Radiochemical methods for determining trace elements); sbornik statey. Moscow, Izd-vo Nauka, 1965, 180-181

TOPIC TAGS: column chromatography, cation exchange resin, alkaline earth metal, radioactivation analysis, neutron bombardment, silica analysis, calcium separation, strontium separation, barium separation

ABSTRACT: A chromatographic method was used to separate calcium, strontium, and barium isolated from samples of silica bombarded with neutrons. The procedure involved the successive elution of the elements adsorbed on a KU-2 cation exchanger (in the NH₄⁺ form) with solutions of trilon B of various pH values. The elution curves are shown in Fig. 1 of the Enclosure. The degree of separation was checked on artificial mixtures containing radioactive tracers. A practically complete separation of Ca, Sr, and Ba and

Card 1/3

L 19352-66
ACCESSION NR: AT5013655

their separation from a large amount of sodium was achieved. The sensitivity of the radio-activation determination of Ca, Sr, and Ba (involving the use of an end-window counter) is: 10^{-7} g for Ca, 9×10^{-8} g for Sr, and 2×10^{-8} g for Ba (the samples had been subjected to a flux of 10^{14} neutrons/cm².sec for 24 hrs.). Although this sensitivity is not very high, the determination has important practical applications. Orig. art. has: 1 figure and 1 table.

ASSOCIATION: None

SUBMITTED: 07Apr64

ENCL: 01

SUB CODE: IC, GL

NO REF SOV: 003

OTHER: 004

Card 2/3

L 19352-66

ACCESSION NR: AT5013655

ENCL: 01




Fig. 1. - Separation of calcium, strontium, and barium on KU-2x15 cation exchange resin in NH₄⁺ form (column diameter 2 mm, height of resin layer 100 mm).

Card 3/3

L 42988-65 EWT(1)/EWT(m)/T/EWA(h) Pz-6/Peb IJP(c) AT
ACCESSION NR: AP5006536 S/0086/65/048/002/0767/0769

AUTHOR: Akimov, Yu. K.; Kalinin, A. I.; Nikitin, V. A.; Pantuyev, V. S.;
Sviridov, V. A.; Sidorov, A. I.; Khachaturyan, M. N.

TITLE: A method for studying elastic pp-scattering in the high energy region
using semiconductor counters

SOURCE: Zhurnal eksperimental'noy i teoreticheskoy fiziki, v. 48, no. 2, 1965,
767-769

TOPIC TAGS: proton scattering, high energy proton scattering, proton semiconductor
counter

ABSTRACT: The possibility of studying high energy proton elastic scattering in the
region of weak transmitted impulses $1.5 \cdot 10^{-3} \text{ GeV}^2/c^2 \leq -t \leq 1.5 \cdot 10^{-1} \text{ GeV}^2/c^2$ using semi-
conductor nuclear particle detectors is shown experimentally. The experiments were
conducted on the synchrophasotron at the Joint Institute of Nuclear Investigations.
The proposed method is applicable for investigations in the region of weak trans-
missions for any reaction of the type $a+b \rightarrow c+d$. In fig. 1 of the Enclosure
(case a), a sharp peak is seen for protons transmitted with an energy of 2.2 Mev.

Card 1/3

L 42988-65

ACCESSION NR: AP5006536

The peak width at the semi-peak points, covering about 330 kev or 15%, was determined basically by Coulomb scattering of protons transmitted to the target and by test geometry. For comparison (case b), the distribution of particles emitted from the same target under identical conditions, along mean free paths in a 125% photographic emulsion, is given. The peak for elastically scattered protons has a halfwidth of $\Delta E/E \approx 18\%$, i.e., somewhat wider scattering than obtained with a semiconductor counter. "In conclusion the authors thank L. I. Lipidus and I. V. Chuvilo for interest in the work, and also V. F. Kushniruk and L. N. Strunov for assistance in the experiment." Orig. art. has: 1 figure, 1 formula.

ASSOCIATION: Ob'yedinenyy institut yadernykh issledovaniy (Joint Institute of Nuclear Investigations)

SUBMITTED: 03Dec64

ENCL: 01

SUB CODE: NP, EC

NO REF SOV: 001

OTHER: 001

Card 2/3


L 42988-65

ACCESSION NR: AF5006536

ENCLOSURE: 01

Fig. 1. Spectra of particles emitted at an angle of 87.7° from a target $(\text{CH}_2)_n$ bombarded by a beam of 10Gev protons: *a*--energy distribution measured with a semiconductor counter; *b*--distribution by mean free paths in a 25% diluted gelatin photoemulsion

Card 3/3



ACC NR: AM5027749	Monograph	UR/ 10
<p>Armand, N. A.; Vvedenskiy, B. A.; Gusyatinskiy, I. A.; Igoshev, I. P.; Kazakov, L. YA.; Kallinan, A. I.; Nazarova, L. G.; Nemirovskiy, A. S.; Prouin, A. V.; Ryakin, E. YA.; Sokolov, A. V.; Tarasov, V. A.; Tashkov, P. S.; Tikhomirov, YU. A.; Troitskiy, V. N.; Fedorova, L. V.; Chernyy, F. B.; Shabel'nikov, A. V.; Shirey, R. A.; Shitrin, YA. S.; Shur, A. A.; Yakovlev, O. I.; Kolosov, M. A.; Levshin, I. P.; Lemkin, A. M.</p>		
<p>Upper tropospheric propagation of ultrashort radio waves (Dal'noye troposfernoye rasprostraneniye ul'trakorotkikh radiovoln) Moscow, Izd-vo "Sovetskoye radio", 1965. 414 p. illus., biblio. 4000 copies printed.</p>		
<p>TOPIC TAGS: radio wave propagation, tropospheric radio wave, radio communication, space communication, tropospheric scatter communication, signal processing, signal distortion, field theory</p>		
<p>PURPOSE AND COVERAGE: This monograph is intended for specialists working in the field of radiowave propagation, designers of long-distance radio communication systems, and teachers and students of the advanced courses in schools of higher technical education. The monograph contains, for the most part, heretofore unpublished results of Soviet experimental and theoretical investigations in the field of long-distance tropospheric ultrashortwave propagation.</p>		
<p>Cord 1/10 V UPC: 621.3N.2Y</p>		

ACC NR:
AN5027749

Problems of investigating the troposphere by means of refractometers, the mean level of signals, meteorological conditions and topography, fluctuation of arrival angles and distortions of antenna directivity patterns, losses in antenna gain, and quick and slow fading of signal levels are discussed. The statistical characteristics of the signals at diversity reception in time, space, frequency and angle as well as the distortion of signals in the communication systems are also investigated. The long-distance propagation theory is analyzed, and the engineering method of calculating field intensity at long-distance tropospheric propagation is given. At present, there is no theory of Long-Distance Tropospheric Propagation which can be applied effectively enough in practice. Thus, in the investigation of that propagation, considerable attention has to be paid to experiments. The special characteristics of geographical conditions of the territory involved should be taken into consideration during the analysis of experimental data and in their practical application because the conditions of propagation in arctic and tropical climates differ from those existing over seas and continents. A considerable part of the monograph deals with the investigations of long-distance tropospheric propagation carried out over dry land routes, 800 km long, in the central part of the USSR under the general supervision of B. A. Vvedenskiy and A. G. Aronberg (up to 1957). V. I. Siforov investigated problems con-

Card 2/10

ACC NR. AM5027749

nected with distortions and fluctuations of signals. References follow each chapter.

TABLE OF CONTENTS:

Foreword --

Ch. I. Radio Engineering Methods of Investigating the Troposphere
Dielectric Constant -- 5

Bibliography -- 16

Ch. II. Results of Troposphere Dielectric Constant Measurements -- 17

1. Relationship between the mean value of the air refraction index and altitude. Standard radio-atmosphere -- 17
2. Fluctuations of the air refraction index -- 24
3. Some notions on the troposphere model -- 43

Bibliography -- 45

Ch. III. Average (mean) Signal Levels in Long Distance Tropospheric Propagation of Ultrashort Waves (L.T.P.U.S.W) -- 48

Card 3/10

ACC NR:
AM5027749

1. Equipment and measuring methods for the mean signal level -- 48
2. Signal attenuation function in LTP USW -- 54
3. Relationship between mean signal level and the distance -- 57
4. Relationship between mean signal level and the wavelength -- 63
5. Relationship of mean signal level and the shadow angles of both transmitting and receiving antennas -- 65
6. Diurnal and seasonal variations of mean signal level -- 72

Bibliography -- 75

- Ch. IV. Effect of Air Refraction Index at the Earth Surface on the Mean Field Level in LTP USW -- 77
 1. Correlation of the mean field level with the air refraction index at the Earth Surface. -- 77
 2. Possibility of predicting field intensity variations -- 81

Bibliography -- 86

- Ch. V. Fluctuation of Radiowave Arrival Angles and Instantaneous Patterns of Antennas Directivities -- 89
 1. Methods of measuring radiowave arrival angles and recording of instantaneous antenna directional patterns -- 89

Card 4/10

ACC NR:
AM5027749

2. Fluctuation of radiowave arrival angles in horizontal and vertical planes -- 92
3. Instantaneous antenna directional patterns -- 92

Bibliography -- 102

Ch. VI. Losses in Antenna Gain of IVP USW -- 103

1. Determination and methods of measuring losses in antenna gain -- 103
2. Experimental data on losses in antenna gain -- 108
3. Theoretical investigations on losses in antenna gain -- 114

Bibliography -- 120

Ch. VII. Theories of Long Distance Tropospheric Propagation of USW -- 122

1. Introductory remarks -- 122

Bibliography -- 129

2. Theory of scattering radiowaves by tropospheric turbulent nonhomogeneities -- 130

Card 5/10

ACC NR:
AM5027749

Bibliography -- 150

3. Reflection of radiowaves from dielectric nonhomogeneities of
definite dimensions -- 151

Bibliography -- 171

4. Reflections of radiowaves from laminated tropospheric nonho-
mogeneities of random character -- 172

Bibliography -- 179

Ch. VIII. Engineering Method of Design-Calculation of Field Intensity

Attenuation -- 180

1. Basic rules of calculation method -- 181

2. Diffraction horizon (a distance, beginning of which, the value
of the field intensity, calculated according to the diffraction
formulas is smaller than the measured intensity) -- 182

3. Determination of field standard attenuation -- 183

4. Meteorological conditions correction -- 184

5. Local topography correction -- 185

6. Estimate of losses in antenna gain -- 185

Card 6/0

ACC NR: AM5027749

7. Estimate of fadings -- 186

Bibliography -- 188

- Ch. IX. Statistical Characteristics of the Envelope, Phase and Frequency of the Random Signal in ITP USW -- 189
1. Statistical characteristics of atmosphere dielectric constant signal components in ITP -- 189
 2. Distribution laws for the envelopes and phase of various signal components -- 193
 3. Distribution laws of sum-signal envelope --
 4. Multi-dimensional distribution functions of instantaneous value of envelopes and phases of the spaced signals in minute intervals 207
 5. Parameters of multi-dimensional amplitude and phase distribution functions of spaced signals -- 210
 6. Statistical characteristics of instantaneous values of the envelopes of spaced signals in minute intervals -- 222
 7. Statistical characteristics of instantaneous values of spaced signal phases in minute intervals -- 239
 8. Statistical characteristics of instantaneous value of phase first derivatives of spaced signals in minute intervals -- 248

Card 7/10

ACC NR: AN5027749

9. Statistical characteristics of instantaneous values of the first derivative of phase in minute intervals -- 257

Bibliography -- 260

Ch. X. Experimental Investigations of Rapid and Slow Fadings in ITP USW -- 262
1. Methods of measuring and processing experimental data -- 262
2. One-dimensional distribution functions of signal instantaneous values -- 264
3. One-dimensional distribution functions of signal averaged values -- 278
4. Period and frequency in rapid fluctuations of signal envelope -- 283

Bibliography -- 287

Ch. XI. Experimental Investigation of Signal Statistical Characteristics at Space, Frequency, Time and Angle Diversity Reception -- 288
1. Space-diversity reception -- 288
2. Frequency-diversity reception -- 295
3. Time-diversity reception -- 299
4. Frequency-time diversity reception -- 305
5. Angle-diversity reception -- 307

Card 8/10

ACC NR AM5027749

Bibliography -- 312

- Ch. XII. Investigation of Amplitude-Frequency and Phase-Frequency
Signal Characteristics at LTP -- 314
1. Measuring and processing methods of experimental data -- 314
2. Amplitude-frequency characteristics -- 321
3. Phase-frequency characteristics of LTP channel -- 325
4. Frequency characteristics of signal group time delay -- 334

Bibliography -- 350

- Ch. XIII. Signal Distortion in LTP USW -- 351
1. Theoretical investigation of distortions appearing in multi-
channel FM LTP communication systems -- 352
2. Experimental investigation of distortion in LTP -- 384
3. Distortions appearing during TV transmission over tropospheric
radio links -- 389

Bibliography -- 392

- Appendix Automation of Signal Statistical Processing -- 394
1. Quantification of continuous signals and coding -- 395
2. Signal quantification instruments -- 397

Card 9/10

MORYGANOV, B.N.; KALININ, A.I.; MIKHOTOVA, L.N.

Polarographic method of studying the thermal decomposition
of acetone diperoxide in organic solvents. Zhur. ob. khim.
32 no.11:3476-3483 N '62. (MIRA' 15:11)

1. Gor'kovskiy gosudarstvennyy universitet im.
N.I. Lobachevskogo. (Acetone) (Peroxides) (Polarography)

BUBNOV, Il'ya Alekseyevich, general-major tekhnicheskikh voysk v
otstavke; KREMP, Adrian Ivanovich, inzh.-polkovnik v
otstavke; KALININ, Aleksandr Konstantinovich, polkovnik;
SHLENNIKOV, Sergey Aleksandrovich, podpolkovnik; DUKACHEV,
M.P., red.

[Military topography; a textbook for military schools of
the Soviet Army] Voennaia topografiia; uchebnik dlia voen-
nykh uchiliishch Sovetskoi Armii. Moskva, Voenizdat, 1964.
349 p. (MIRA 17:7)

KALININ, A.L.; KALININA, M.Ya.

Using the potential regulator. Fiz. v shkole 20 no.6:72-73 N-D '60.
(MIRA 14:2)

1. 29-ya srednyaya shkola, Novosibirsk.
(Voltage regulators)

KALININ, A. V.

LA 31011

USSR/Medicine - Gas Gangrene

Feb 53

"Concerning the Rapid Detection of *B. perfringens*,"
A.M. Kalinin, Ye.F. Rosenfel's, S.M. Lisyanskaya,
Chair of Microbiol, State Order of Lenin Inst for
Advanced Training of Physicians imeni S.M. Kirov,
Leningrad

"Zhur Mikrobiol, Epidemiol, i Immunobiol" No 2,
pp 59, 60

Describes detection of *B. perfringens* in various
media both in the presence and absence of bacterial
antagonists. Finds the use of peptone-milk medium
(proposed in 1944 by A. M. Kalinin) of advantage
for this diagnostic procedure.

246T14

KALININ, A.M., professor.

Staphylococcal septic process with varying localization of the pathogen; experimental research. Akush. i gin. no. 4:43-48 Jl-Ag '55.
(MLRA 8:11)

1. Iz Instituta akusherstva i ginekologii (dir.prof. P.A. Beloshapko) Akademii meditsinskikh nauk SSSR.
(MICROCOCCUS, infect.
exper. eff. of localization of carrier on septic process)

Kalinin, A. M.

V 1738⁴ Ferroelectric Properties of Solid Solutions (Pb,Bi)
SnO₃, Pb(11,Sn)O₃, and Pb(Zr,Sn)O₃. Segnetoelektricheskoe
avtovata tverdukh rastvorov (Pb,Ba)SnO₃, Pb(Ti, Sn)O₃,
and Pb(Zr, Sn)O₃. (Russian.) G. A. Smolenskii, A. I. Aranovich,
A. M. Kalinin, and T. M. Fedotova. *Zhurnal Tekhnicheskoi
Khimii*, v. 25, no. 12, Oct. 1955, p. 2131-2142.

PH Experimental investigation, including the preparation of test
specimens. Analysis of results. Tables, graphs. 11 ref.

KALININ, A. N.

KALININ, A. N.

Locks (Hydraulic Engineering)

Model of a lock. Geog. v. shkole No. 3, 1952.

Monthly List of Russian Accessions, Library of Congress, September 1952, UNCLASSIFIED.

KALININ, Aleksandr Nikolayevich.; CHUVICHKIN, Sergey Pavlovich.; BEZRUCHENKO, S.P., red.; ALEKSANDROV, L.A., red. izd-va.; TIKHONOV, Ye.A., tekhn. red.

[Auxiliary machinery of ships] Sudovye vspomogatel'nye mekhanizmy. Moskva, Izd-vo "Morskoi transport," 1957. 209 p. (MIRA 11:12)
(Ships--Equipment and supplies)

KALININ, A.N.

Settling of mineral soils in railroad embankment beds. Transp.stroi.
7 no.8:21-22 Ag '57. (MIRA 10:12)

1. Glavnny geolog ekspeditsii Lengiprotransa.
(Soil mechanics) (Railroads--Earthwork)

KALININ, A.N.

Replacing heaving grounds in roadbed excavations and embankments.
Transp. stroi. 7 no.11:18-20 N '57. (MIRA 11:2)

1. Glavnny geolog ekspeditsii Lengiprotransa.
(Railroads--Track)

KALININ, A.N.

Causes of one-sided heaving. Transp. stroi. 8 no. 7:28-29 J1 '58.
(MIRA 11:?)

1. Glavnyy geolog ekspeditsii Lengiprotransa.
(Railroads--Earthwork)
(Soil mechanics)

KALININ, A.N., inzh.

Deformation of buildings in regions with a climate.
Transp.stroi. 10 no.8:36-37 Ag '60.

(MIRA 13:8)
(Vorkuta region--Foundations)

KALININ, A.N.

Deformations of buildings in regions subject to severe weather
conditions. Stroi. v raion. Vost. Sib. i Krain. Sev. no.1:64-68
'61. (MIRA 17:11)

KALININ, A. N.

Forestry Schools and Education

First graduation of young specialists from the Lubensk forestry high school. Les.
khoz. 5 No. 4, 1952.

9. Monthly List of Russian Accessions, Library of Congress, August 1952 Uncl.

KALININ, A.N. [deceased]

A device for exercises in orientation. Geog. v shkole 21 no. 1:52
Ja-F '58. (MIRA 11:7)

1. Shkola no. 123 g. Leningrada.
(Physical geography--Audio-visual aids)

KALININ, A.P.; KASHAYEVA, A.N.

Machining end teeth of couplings using gear shaping techniques.
Stan. i instr. 34 no.9:33 S '63. (MIRA 16:11)

KALININ, A.P., mekhanik puteukladochnogo krana

Increasing the operative efficiency of tracklaying machinery.
Put' i put. khoz. 7 no.11:12 '63. (MIRA 16:12)

1. Putevaya mashinnaya stantsiya No.99, stantsiya, Pocheb,
Moskovskoy dorogi.

NIKOLAYEV, O.V.; MEN'SHIKOV, V.V.; KALININ, A.P.; ZHURAVKO, S.K.;
BOL'SHAKOVA, T.D.; GERASIMENKO, F.F.; CHURILOVA, A.I.,
red.

[Pheochromocytoma] Feokhromotsitoma. [By] O.V.Nikolaev
i dr. Meckva, Meditsina, 1965. 235 p. (MIRA 18;2)

KALININ, A.P., kandidat meditsinskikh nauk
www.sovietmedicine.com

Lymphosarcoma of the colon. Vop. onk. 2 no.1:95-97 '56 (MLRA 9:4)

1. Iz akushersko-ginekologicheskoy kliniki (dir.-prof. N.Ye. Sidorov)
1 2-y khirurgicheskoy kliniki (dir.-dotsent V.N. Pomosov) Kasanskogo
gosudarstvennogo instituta dlya usovershenstvovaniya vrachey imeni
V.I. Lenina.

(COLON, neoplasms

lymphosarcoma)

(LYMPHOSARCOMA

colon)

KALININ, A.P., (Kazan', ul. Nekrasova, d. 11, kv. 5)

Cases of metastases of gastric cancer. Vop. onk. 3 no.1:93-96 '57
(MLRA 10:4)

1. Iz II kafedry khirurgii (zav.-prof. P.V. Kravchenko) Kazanskogo
gosudarstvennogo instituta usovershenstvovaniya vrachey im. V.I.
Lenina.

(STOMACH NEOPLASMS, case reports
metastases to uterus, surg.)
(UTERUS NEOPLASMS, case reports
metastatic from stomach, surg.)

KALININ, A.P.

Reduction gear driving for a feeding rack. Zhur.vys.nerv.deiat. 7
no.1:146-147 Ja-^Y '57. (MIRA 10:10)

1. Vtoraya kafedra khirurgii Kazanskogo gosudarstvennogo instituta
dlya spetsializatsii i usovershenstvovaniya vrachey i kafedra pato-
fiziologii Kazanskogo meditsinskogo instituta.

(REFLEX, CONDITIONED

reductor control of feeding racks for prod. of reflexes
(Rus))

KALININ, A.P., kandidat meditsinskikh nauk

Stomach resection for bleeding neurinoma. *Khirurgija* 33 no.2:108-109
F '57.
(MLRA 10:6)

1. Iz 2-y kafedry khirurgii (sav. - prof. P.V.Kravchenko) Kazanskogo
gosudarstvennogo instituta usovershenstvovaniya vrachey imeni V.I.
Lenina i Kanashskoy lineynoy bol'nitsy (nachal'nik G.V.Kalechits).
(GASTRECTOMY, in various dis.

hemorrhagic neurilemmoma of stomach (Rus))
(NEURILEMMOMA, surg.)

hemorrhagic of stomach, gastrectomy (Rus))
(STOMACH NEOPLASMS, surg.)

hemorrhagic neurilemmoma, gastrectomy (Rus))

KALININ, A.P., kand.med.nauk

Genital tuberculosis and tuberculosis of the peritoneum [with
summary in French]. Probl.tub. 36 no.3:98-100 '58 (MIRA 11:5)

1. Iz akushersko-ginekologicheskoy kliniki (dir. - prof. N.Ie. Sidorov) i vtoroy khirurgicheskoy kliniki (dir. - prof. P.V. Kravchenko) Kazanskogo instituta usovershenstvovaniya vrachey im. V.I. Lenina.

(TUBERCULOSIS, FEMALE GENITAL, in pregn.
with postpartal tuberc. peritonitis (Rus))
(PERITONITIS, etiol. & pathogen.
postpartal, caused by tuberc. of genitalia (Rus))

KALININ, A.P., kand.med.nauk (Kazan')

Morphological criteria of malignant degeneration of benign adenomas of the thyroid gland. Probl.endok. i gorm. 5 no.3: 51-56 My-Je '59. (MIRA 12:9)

1. Iz 2-y kafedry khirurgii (zav. - prof.P.V.Kravchenko) Kazanskogo gosudarstvennogo instituta usovershenstvovaniya vrachey imeni V.I.Lenina (dir. - prof.I.V.Danilov) i morfologicheskogo otdela (zav. - prof.Ye.I.Tarakanov) Vsesoyuznogo instituta eksperimental'noy endokrinologii (dir. - prof.Ye.A. Vasynukova).

(THYROID GLAND, neoplasms
adenoma, morphol. criteria of malignant degen.
(Rus))

KALININ, A.P., kand.med.nauk; VOLOGINA, N.A. (Kazan')

On the problem of hyperinsulinism. Probl.endok.i gorm. 5
no.5:93-96 S-0 '59. (MIRA 13:5)

1. Iz Kazanskoy psikhonevrologicheskoy bol'nitsy (glavnnyy vrach
F.F. Davletshin) i II kafedry khirurgii (zav. - prof. P.V.
Kravchenko) Kazanskogo gosudarstvennogo instituta usoverhenstvo-
vaniya vrachey imeni V.I. Lenina.

(HYPERINSULINISM case reports)

KALININ, A.P., kand.med.nauk

Forcible eventration with avulsion of part of the small intestine
in toxicoinfectious psychosis. Kaz.med. zhur. 40 no.4:80-81 Jl-Ag '59.
(MIRA 13:2)

1. Iz 2-y kafedry khirurgii (zaveduyushchiy - prof. P.V. Kravchenko)
i kafedry akusherstva i ginekologii (zaveduyushchiy - prof. N.Ye.
Sidorov) Kazanskogo Gosudarstvennogo instituta dlya spetsializatsii
i usovershenstvovaniya vrachey imeni V.I. Lenina.
(INTESTINES--WOUNDS AND INJURIES)
(PSYCHOSES)

RADBIL', O.S., dotsent; KALININ, A.P., kand.meditinskikh nauk

Clinical use of royal jelly. Kaz. med. zhur. 41 no.3:87-91 My-Je
'60.
(MIRA 13:9)

1. Iz 2-y kafedry terapii (zav. ~ dotsent O.S.Radbil') i 2-y
kafedry khirurgii (zav. ~ prof. P.V.Kravchenko) Kazanskogo gosudar-
stvennogo instituta dlya usovershenstvovaniya vrachey im. V.I. Lenina.
(ROYAL JELLY)

KALININ, A.P.

Putty for attaching a salivary balloon. Zhur. vys. nerv. deiat.
10 no. 3:479-480 My-Je '60. (MIRA 14:2)

1. Second Chair of Surgery, Kazan' Institute for Medical Advanced
Training and Chair of Pathophysiology, Kazan' Medical Institute.
(CONDITIONED RESPONSE) (PHYSIOLOGICAL APPARATUS)

KALININ, A.P., kand.med.nauk; TSAREV, N.P.

Complications after vaccination. Sov.med. 25 no.1:127-130 Ja '61.
(MIRA 14:3)

1. Iz kafedry khirurgii i neotlozhnoy khirurgii (zav. - prof. P.V. Kravchenko) Kazanskogo gosudarstvennogo instituta usovershenstvovaniya vrachey imeni V.I.Lenina i Kanashskoy lineynoy bol'nitsy (nachal'nik G.V.Kalechits).

(VACCINATION)

KALININ, A.I., kand.med. nauk ; BALABOLKIN, M.I. (Moskva)

Troell-Junet syndrome. Vrach. delo no.9:145-147 S:63.

(MIRA 16:10)

1. Khirurgicheskoye otdelenie (zav. prof. O.V.Nikolayev)
Vsesoyuznogo nauchno-issledovatel'skogo instituta eksperi-
mental'noy endokrinologii.

(ACROMEGALY) (GOITER)

KALININ, A.P., kand. med. nauk; TALANTOV, V.V.

Schoenlein-Henoch disease and thyrotoxicosis. Sov. med. 27
no.11:92-96 N '63 (MIRA 18:1)

1. Iz khirurgicheskogo otdeleniya (zav. - prof. O.V.Nikolayev)
Vsesoyuznogo nauchno-issledovatel'skogo instituta eksperimental'-
noy endokrinologii (direktor - prof. Ye.A. Vasjukova).

PINSKIY, S.B. (Irkutsk, ul. Marata, 25, kv.14); KALININ, A.P. (Moskva, V-36, 1-ya Cheremushkinskaya ul., 13, korp. 2, kv.50)

Cancer of the thyroid gland in children. Vop. onk. 10 no.3:
72-77 '64. (MIRA 17:8)

1. Iz khirurgicheskogo otdeleniya (zav. - prof. O.V. Nikolayev) Vsesoyuznogo instituta eksperimental'noy endokrinologii (dir. - prof. Ye.A. Vasyukova).

KALININ, A.P., kand. med. nauk; PINSKIY, S.B. (Moskva)

Pathology of the thyroglossal duct. Probl. endok. i gorm. 10
no.1:25-28 Ja-F '64. (MIRA 17:10)

1. Khirurgicheskoye otdeleniye (zav. - prof. O.V. Nikolayev)
Vsesoyuznogo instituta eksperimental'noy endokrinologii (dir.-
prof. Ye.A. Vasyukova).

NIKOLAYEV, O.V., prof.; KALININ, A.P., kand. med. nauk; VEYNBERG, E.G.

Surgical treatment of hyperinsulinism. Khirurgiia 40 no.2:134-
140 F '64. (MIRA 17:7)

1. Khirurgicheskoye otdeleniye (zav. - prof. O.V. Nikolayev)
Vsesoyuznogo instituta eksperimental'noy endokrinologii
(direktor - prof. Ye.A. Vasyukova), Moskva.

PEREPUST, L.A.; IOFFE, B.N.; KALININ, A.P. (Kosikva)

Roentgenological data on the state of the adrenal glands in
Itsenko-Cushing disease and diencephalic syndrome pursuing the
course of Itsenko-Cushing disease. Probl. endok. i norm. 9 no. 6:
75-80 N-D '63. (USA 17:11)

1. Iz rentgenologicheskogo otdeleniya (zav. - doktor med. nauk
M.I. Santotskiy) i khirurgicheskogo otdeleniya (zav. - prof.
O.V. Nikolayev) Vsesoyuznogo instituta eksperimental'noy endo-
krinologii (dir. - prof. Ye.A. Vasyukov).

ODINOKOVA, V.A. ; KALININ, A.P. (Moskva)

Hurthle cell tumors of the thyroid gland. Arkh. pat. 26 no.4:41-45
'64. (MIRA 18:7)

1. Patologoanatomicheskiy otdel (zav. - chlen-korrespondent AMN SSSR prof. A.P. Avtsyn) Moskovskogo oblastnogo nauchno-issledovatel'skogo klinicheskogo instituta imeni Vladimirovskogo i khirurgicheskoye otdeleniye (zav. - prof. O.V. Nikolayev) Vsesoyuznogo instituta eksperimental'noy endokrinologii.

NIKOLAYEV, O.V., prof.; KALININ, A.P., kand. med. nauk; KAPETEV, L.N.

Clinical aspects, diagnosis and surgical treatment of pheochromocytoma. Khirurgija 40 no.7:83-87 Jl '64.

(MIRA 18:2)

1. Khirurgicheskye otdeleniya (zav. - prof. O.V. Nikolayev) Vsesoyuznogo instituta eksperimental'noy endokrinologii (dir. - prof. Ye.A. Vasyukova), Moskva.

KALEININ, A.P.; BALABOLKIN, M.I.

Syndrome of hypercorticalism in malignant tumors of different organs.
Vop. onk. 11 no.10:114-120 '65. (MIRA 18'10)

KALININ, A.P.; SHAKHNOVSKAYA, V.F.; ZARETSKIY, M.N.

Pregnancy and labor in Itsenko-Cushing's disease. Probl. endok.
i gorm. 11 no.6:13-17 N-D '65. (MIRA 18:12)

1. Terapevticheskoye otdeleniye (zav. - kand. med. nauk A.G.Vesi-
l'yeva) i khirurgicheskoye otdeleniye (zav. prof. O.V.Nikolayev)
Instituta eksperimental'noy endokrinologii AMN SSSR, Moskva.

RADBUL', O.S., prof.; KALININ, A.P., kand. med. nauk

Antibacterial action of royal jelly. Veterinariia 41 no.22-24 D '64.
(MIRA 18:9)

KALININ, A.P., mekhanik kranov; TATARINOV, V.A., mekhanik kranov

Speeding up tracklaying operations. Put' 1 put. khoz. 9 no.10;26 '65.
(MIRA 18;10)

1. Stantsiya Bryansk II, Moskovskoy dorogi.

KALININ, Anatoliy Semenovich

(L'vov State Veterinary-Zootechnical Inst) Academic Degree of Doctor of Veterinary Sciences, based on his defense, 3 July 1954, in the Council of the Kazan' State Veterinary Inst imeni Bauman, of his dissertation entitled: "Cythological composition and myelogram of the sternal puncture content of the healthy horse."

Academic degree and/or title: Doctor of Sciences

SO: Decisions of VAK, List no. 24, 26 Nov 55, Byulleten' MVO SSSR, No. 20, Oct 57, Moscow, pp 22-24, Uncl. JPRS/NY-471

1. KALININ, A. S.
2. USSR (600)
4. Looms
7. Unit repairs of weaving equipment. Tekst. prom. 12 no. 10, '52.

9. Monthly List of Russian Accessions, Library of Congress, January 1953. Unclassified.

KALININ, A.S.

Some characteristics of the greisenisation process in the
Komsomol'sk deposit. Dokl. AN SSSR 157 no.6:1379-1381 Ag
'64. (MIRA 17:9)

1. Irkutskiy gosudarstvennyy nauchno-issledovatel'skiy institut
redkikh metallov. Predstavлено академиком D.S. Korzhinskим.

6.01. XIX. 1964

Orthoclase-quartz vein complex in a molybdenum deposit.
Dokl. AN SSSR 159 no.1:102-105 N '64. (MIRA 17:12)

I. Institut zemnoy kory Sibirskego otdeleniya AN SSSR.
Predstavleno akademikom D.S. Korzhinskim.

KALININ, A. T. and MINKEVICH, A. N.

"Development of the Process of Liquid Carburizing (Cyaniding) Steel,"
pp 81/99 in Modern Methods of Heat Treating Steel by Com Inzhenera i Tekhnika
imeni F E Dzerzhinskovo. Gosudarstvennoye Nauchno-Tekhnicheskoye Izdatel'stvo
Mashinostroitel'noy Literatury, Moscow (1954) 404 pp.

Evaluation B-86350, 30 Jun 55

Kutu
Chernov

Institute of Chemistry, Moscow University
A. T. Kabanin, M. N. Kurnakov, and A. V. Chernov
Berdichevsky, *Polymer Sci.*, 1938, No. 11, 10-9. During
catalytic hydrogenation of hydrocarbons used for it are decomposed to
C, H₂, and CH₄ or form aromatics and coke, both types of
reactions being undesirable from the carbonization standpoint.
According to their tendency towards decomposition they can be ranged as paraffins, olefins, naphthenes, and
aromatics; while in the light of their tendency towards
carbonization, this order is inverted. Since natural gas in
Russia is Rumania, synthetic hydrocarbons were made by the
 $2\text{CH}_3 + \text{CO} \rightarrow \text{C}_2\text{H}_6 + \text{H}_2\text{O}$ reaction and then hydro-
genated to C₂H₆. (process not described), forming a
mixture of paraffins, b.p. 40-40° called Saitta. Its carbonizing
characteristics were compared with those of other hydrocarbons
and were found to be better. D. G.

Moscow Autochemistry Inst *WT*

"APPROVED FOR RELEASE: 03/20/2001

CIA-RDP86-00513R000620030010-9

KALININ, A. I.

✓ Gas granulation and agglomeration. 18
Zeitschr. für N. M. Kalandinskij. U.S.S.R. 105, 426, 1957.
Date Dec. 1957. Nitridation is carried out in triethylaluminum,
the nitride of which is controlled by a suitable catalyst.

4E2 CH

APPROVED FOR RELEASE: 03/20/2001

CIA-RDP86-00513R000620030010-9"

KALININ A. T.

ASSONOV, Aleksandr Denisovich, kand.tekhn.nauk; KALININ, A.T., kand.tekhn.
nauk, retsenzent; PASTERNAK, N.A., kand.tekhn.nauk, red.;
YEGORKINA, L.I., red.izd-va; BL'KIND, V.D., tekhn.red.

[Technology of the heat treatment of automobile parts] Tekhnologiya
termicheskoi obrabotki detalei avtomobilja. Moskva, Gos. nauchno-
tekhn.izd-vo mashinostroit. lit-ry, 1958. 263 p. (MIRA 11:4)
(Metals--Heat treatment)
(Automobile industry)

KHANININ, A. F.

卷之三

(left page). Dr. A. Geller, Director of Technical Services; Mr. (Taddeus) H. Ritter, Research Director; Prof. Dr. B.J. Norden, Managing Mgr. for Laboratories on Steel, Corrosion and Steel Making; B.U. Research Team, Bremen.

This collection of 50 articles, compiled by 23 authors, aims to acquaint the reader with modern practice in the best treatment of steels. The authors are generally concerned with the development of various types of structural steels and have paid great study and work to the design of their alloying elements. The mechanical evolution is described as well as the new lengths. The particularities of titanium and titanium alloys are discussed. The book is thoroughly descriptive, giving a good deal of the material on which the author has based his conclusions. It is intended to give details of the scientific control of heat-treatment processes and the mechanical properties of the different kinds of steels. There are numerous tables and diagrams. Bibliographies, literature, prices of the steel and chapters are included. The articles comprising this collection are reprints from American and British periodicals, and technical journals.

प्राचीन ग्रन्थों का संक्षेप

Period 1946, No. 6. Proper Selection of Steels for Cold-worked Parts Gartshore, F.T. Initial Data for Selecting Steels for the Coldworking and Drawing of Cold-worked Parts Hollister, A.G. A Modern Characterizing Agent for the Coldworking and Drawn Metal Products, O.R. MacEachern, and P.T. St. Leger. Properties and Quality of Drawn-shaped Spring Steels Waller, W.A. Improvements in the Composition and Some Developments of Tool Steels Waller, W.A. An Investigation of 100Cr3 Lowalloy Steel as a Material for Casting Steels Zimmerman, A.G. New Types of High-speed Steels Zimmerman, A.G. Hardening and Tempering of High-speed Steels With Induction	95 269 271 273
---	-------------------------

卷之三

APPROVED FOR RELEASE: 03/20/2001

CIA-RDP86-00513R000620030010-9"

SOV/137-59-3-7025
Translation from: Referativnyy zhurnal. Metallurgiya, 1959, Nr 3, p 299 (USSR.)

AUTHOR: Kalinin, A. T.

TITLE: New Developments in the Technology of Gas Carburizing and Gas Nitriding (Novoye v tekhnologii gazovoy tsementatsii i gazovogo tsianirovaniya)

PERIODICAL: V sb.: Materialy Soveshchaniya g'avn. metallurgov z-dov i in-tov avtomob. prom-sti. Nr 3 Moscow, 1958, pp 95-127

ABSTRACT: Modern domestic and foreign methods of obtaining controlled carburization atmospheres are described together with such automatic devices for regulation of C potential as the endothermic generator and the "Carbotronic" apparatus, employed if natural gas is available, and soot-free liquid carburizers and the "Carboohm" device employed if natural gas is not available. A GIAP-3 catalyzer replacing granulated Ni, which proved inadequate, was tested in the endothermic generator at the thermo-chemical laboratory of the NIITavtoprom. The GIAP-3 permits the generation of gas at the relatively low temperature of 950°C instead of 1100°. Graphs were plotted representing the dew point and the gas composition as

Card 1/2

SOV/137-59-3-7025

New Developments in the Technology of Gas Carburizing and Gas Nitriding

functions of the air/natural-gas ratio. The GIAP-3 loses its activity as it is gradually contaminated with S. For purposes of decontamination of the gas two absorber units based on ZnO and operating at a temperature of 400° were tested together with GIAP-10 (ZnO pellets) and a spent Zn-Cr catalyst of methanol synthesis. The latter is inexpensive (~1000 rubles per ton) and proved to be more profitable. Synthol was successfully tested as a liquid carburizer, but isobutyl was found to be even better because it does not produce soot in the process of cracking. The following hydrogen-free compounds containing additions of alcohol serving to reduce the amount of soot were tested for purposes of gas nitriding: Urotropine, pyridine, aniline, and orthotolididine. The following compounds containing hydrogen were also tested: Formamide, nitrobenzene, and triethanolamine. The latter proved to be the most suitable. The C potential may be controlled by means of adding water and alcohol to the triethanolamine. Muffle-less furnaces are recommended when soot-free carburizers and nitriding agents are employed.

A. S.

Card 2/2

SOV/137-58-10-21282

Transaltion from: Referativnyy zhurnal, Metallurgiya, 1958, Nr 10, p 120 (USSR)

AUTHORS: Gurevich, I. L., Dybovskiy, R. K., Kalinin, A. T., Veselov, B. P.

TITLE: Liquid Carburizer for Gas Carburization of Steel (Zhidkiy karburizator dlya gazovoy tsementatsii stali)

PERIODICAL: Materialy Mezhvuz. nauchn. soveshchaniya po vopr. novoy tekhn. v neft. prom-sti, 1958, Vol 3, pp 206-223

ABSTRACT: An investigation was conducted on the gas carburization (GC) of specimens of Nr-20 and 18KhGT-grades of steel in a laboratory furnace and in a small type Ts-25 shaft kiln using various liquid carburizers (C); lamp kerosene was used as the standard C. It is indicated that at GC temperatures of 925 - 930°C, a duration of 1.5 hours or 5 hours and at the optimum feeding rate for each C, the employment of alkane C ensures advantages over the use of aromatic C in the total depth of the layer, the magnitudes of the transitional and eutectoid zones, and the degree of carburization of a control wire 1.5 mm in diameter. The best results were obtained using synthol with a boiling-point range of 48 - 246°. When sooty products of decomposition of C are present in the muffle, GC showed that alkane C,

Card 1/2

SOV/137-58-10-21282

Liquid Carburizer for Gas Carburization of Steel

especially synthols with 48 - 246° and 69 - 302° boiling-point ranges, decrease the carburizing capacity less than the aromatic C. The greatest evolution of coke-soot was produced by the aromatic C. Comparative data on GC of machine parts of the DT-54-type tractor of 18KhGT-grade steel in continuous furnaces of the heat-treatment shop of the KhTZ [Khar'kovskiy Traktorny Zavod (Khar'kov Tractor Plant)] showed that compared to the employment of kerosene the increase in the productivity for 100 - 231°, 101 - 305°, and 195 - 312° fractions are by 24, 51, and 40%, respectively, while the decreases in the amount of the coke-soot deposition are by 50, 35, and 41%, respectively. When synthols are used, a loose soot is produced which is easily washed off with the oil in quenching tanks, corrosion produced by the presence of S is prevented, and the consumption of C per operation is decreased. Technical specifications (TU 574 - 55) are developed for two types of C: synthol 100 - 300° for continuous furnaces and synthol 100 - 230° for shaft kilns.

1. Steel--Carbonization 2. Kerosene--Performance

L. F.

Card 2/2

NOVIKOVA, A.Ya.; LEVITANSKAYA, N.M.; KALININ, A.T.

Defects of the cyanide hardening layer and factors contributing
to their formation. Avt.prom. no.3:39-41 Mr '61. (MIRA 14:3)

1. Nauchno-issledovatel'skiy eksperimental'nyy institut avtotraktornogo
elektrooborudovaniya i priborov.
(Cyanide process)

KALININ, A.T., kand. tekhn. nauk; MARKOV, L.A., red.; ALEKSEIEVA, T.V.,
tekhn. red.

[Use of controlled atmospheres in heat treatment] Primenenie kontro-
liruemых atmosfer pri termicheskoi obrabotke; obzor. Moskva,
TSentr. in-t nauchno-tekhn. informatsii mashinostroenia, 1961. 99 p.
(MIRA 14:10)
(Furnaces, Heat-treating) (Protective atmospheres)


S/129/61/000/008/015/015
E073/E535

AUTHORS: Kalinin, A.T., Candidate of Technical Sciences,
Ivanyuk, M.Ya., Engineer and Ovanesyan, S.A., Engineer

TITLE: Sulphiding in baths without using cyanide salts

PERIODICAL: Metallovedeniye i termicheskaya obrabotka metallov,
1961, No.8, pp.56-58

TEXT: Sulphiding is not used on a wide enough scale in the Soviet Union in view of difficulties encountered with application of cyanide salts. To overcome these difficulties NIITavtoprom developed a technology which does not involve the use of cyanide salts. Gas sulphiding did not yield positive results due to the fact that toxic gases with an unpleasant smell formed. In the process of liquid cyaniding (at 560-580°C) the poisonous salt KCN is substituted by KCNO and the process of sulphiding will proceed according to the reactions




Card 1/3


Sulphiding in baths

S/129/61/000/008/015/015
E073/E535

and during the process carbon and nitrogen will also form in accordance with the reaction



In NII Tavtoprom the cyanate was obtained from the two salts: urea (55%) and potash (45%) in accordance with the following reaction



The urea and the potash are introduced in small quantities into an iron crucible heated to 350-380°C. During the fusion process sal ammoniac and carbon dioxide are generated and a 98% potassium cyanate is obtained. When the crucible is three-quarters full the temperature is increased to 500°C and sodium sulphide is added. The bath is ready for operation when the sulphide sulphur in the melt reaches 0.2-2%. The content of potassium cyanate in the melt should not be below 30%. The effect of this process was tried out on piston rings in repaired truck engines. It was found that by means of this treatment the service life of the

Card 2/3

Sulphiding in baths ...

S/129/61/000/008/015/015
E073/E535

piston rings increased from the standard 10-12000 km to 30000 km. Details are given on the sequence of operations of this sulphiding process. For components which must not be heated to temperatures exceeding their tempering temperature, a chemically active low temperature bath was developed consisting of 90% KCNS + 10% NH₄CNS. The sulphiding process is carried out in a gaseous medium formed by the decomposition of ammonium thiocyanate salts. As a result, the melt retains its fluidity and no ballasts form. This process is suitable, for instance, for worm gears and other case-hardened components.

ASSOCIATION: NIITavtoprom

Card 3/3